



PREMIUM RANGE 200 Series

Product Overview

SVS207MWQ 7" IP68 H/Duty Quad Camera Monitor



PRODUCT SPECIFICATION

- 7" Digital TFT LCD wide panel
- Water resistant (IP68)
- Auto NTSC/PAL detection
- Auto Day/Night detection
- 4 camera inputs, 1AV input, 1 video output
- Capacitive touch key
- Parking distance marker setting
- Adjustable speed switch

Offering all of the specs as the 207MW the 207MWQ is capable of displaying up to four camera inputs at any one time on the 7" TFT LCD display. The user is able to select from a range of different views ranging from single to quad can adjust camera settings through the comprehensive on screen display menu. The IP rating on this screen make sit the ideal choice for all applications where quality is essential.



Multivolt



Audio



Suits all
P1
Cameras



4 Cameras



OSD
MENU



7"
SCREEN



IP68



Parking Marker
Display



Multiple Camera
Display

- Operating Temperature: -25°C to +75°C
- Supports various divide modes
- Supports multi-function camera (normal/shutter/tilt)
- Operating Voltage: DC10~32V
- Resolution: 800 x 480
- Removable sun shield
- Weight Approx: 680g
- External Dimensions: 195(W)X124(H)X30(D)