

100
Series

SVS100DC Dome Camera



Product Information

On first glance one of the great things about our dome camera is its small and unobtrusive size - measuring a mere 50mm in diameter and made from Aluminium. The SVS100DC is also hard anodised and powder coated for added protection.

The camera features a fully adjustable 'Shake Proof' cup style bracket, and houses a high resolution camera module with 6 IR LED's that switches on automatically in low light conditions to provide visibility in dark conditions, making it perfect for a wide range of applications where neat integration and various viewing positions are required.

Features svS100DC

- **Nightvision up to 5 meters**
- **6 Infra-red LEDs**
- **Wider viewing angle up to 120°**
- **Compact profile**
- **IP69K**

Specifications

Image	Interline transfer type CCD
Picture Element	NTSC: 512 x 492 pixels PAL: 512 x 582 pixels
Image Size	1/3 inch
Lens	120°
Synchronisation	Internal
Horizontal Resolution	420 TV lines
Minimum Illumination	0.1 Lux (day), 0 Lux (with IR)
Signal to Noise Ratio	48 dB
White Balance	Auto
Electronic Shutter	1/60 (NTSC) / 1/50 (PAL) ~ 1/10,000 Seconds
Power Supply	DC 12V
Power Consumption	Max. 150 mA
Vibration	10G
IP Rating	IP69K
Operational Temperature	-20°C ~ +70°C, RH 95% MAX.
Case Material	Aluminium
Weight	150gm
Dimensions	50mm W x 55mm D
Supplied Accessories	Manual & Alan Key