

100
Series

SVS109MOE 2 camera SVS109MQ Quad screen 4 Camera 9" Monitor 2 or 4 camera input



Product Information

9" Monitor dash mount with 2 or 4 Camera input option LCD screen - Available in 2 Camera input with single display or QUAD screen with 4 camera inputs. Reverse polarity protected and with a high brightness and contrast means the screen is visible in daylight conditions. Available with 'U' bracket for heavier duty mounting or a pad mount as required.. Monitor has PAL/NTSC auto switching which means it compatible with both camera input types PAL/NTSC. With trigger wires allowing for auto switching between cameras and can be set to use reversing lines if required. Designed to give more visibility by offering a larger screen. This is designed to cope the harsh treatments of our Australian working environments and has a wide voltage range



Features

- **9"LCD Monitor**
- **16:9wide screen**
- **Reverse guide**
- **Auto on when triggered**
- **Dash mount**
- **12-32V Monitor**

Specifications

Screen Size	9"LCD
Resolution	800 x 3 (RGB) x 480 Pixel
TV System	Auto PAL/NTSC
Voltage	12-32VDC
Interface	Analog
Working Temperature	-20°C ~ +70°C
Viewing Angle	50deg 60deg 70deg
Impact rating	10G Shock