

Product Information

September 2015

Safety Through Vision



SVS200SC Heavy Duty Square Camera





Features

- CCD IR LED Colour Camera
- Optical Axis Correction
- Waterproof IP69K
- Light control by Ambiance Luminance
- Extra-wide Field of View
- 12V DC
- Ultra Performance in Low Light more than 20m
- Normal/Mirror Image Switching (Patent Listed)
- Vandal Resistance
- Built in Microphone

Specifications

Image Device1/3" CCDPicture Element470, 000 pixelsAngle of ViewDiagonal 130°Minimum Illumination0 Lux. (IR LED ON) W/ IR LEDSignal to Noise RatioBetter than 50dB(at AGC off)Horizontal ResolutionNTSC: More than 480NTV lines/PAL: More than 530TV linesWaterproofIP69KPower InputInput Voltage DC 12VVibration7GShock100GOperating Temperature-40°C ~ +80°C	Image Device	1/07 000
Angle of ViewDiagonal 130°Minimum Illumination0 Lux. (IR LED ON) W/ IR LEDSignal to Noise RatioBetter than 50dB(at AGC off)Horizontal ResolutionNTSC: More than 480NTV lines/PAL: More than 530TV linesWaterproofIP69KPower InputInput Voltage DC 12VVibration7GShock100G	Image Device	I/3" UUD
Minimum Illumination0 Lux. (IR LED ON) W/ IR LEDSignal to Noise RatioBetter than 50dB(at AGC off)Horizontal ResolutionNTSC: More than 480NTV lines/PAL: More than 530TV linesWaterproofIP69KPower InputInput Voltage DC 12VVibration7GShock100G	Picture Element	470, 000 pixels
Signal to Noise Ratio Better than 50dB(at AGC off) Horizontal Resolution NTSC: More than 480NTV lines/PAL: More than 530TV lines Waterproof IP69K Power Input Input Voltage DC 12V Vibration 7G Shock 100G	Angle of View	Diagonal 130º
Horizontal ResolutionNTSC: More than 480NTV lines/PAL: More than 530TV linesWaterproofIP69KPower InputInput Voltage DC 12VVibration7GShock100G	Minimum Illumination	0 Lux. (IR LED ON) W/ IR LED
Honzontal Resolution 530TV lines Waterproof IP69K Power Input Input Voltage DC 12V Vibration 7G Shock 100G	Signal to Noise Ratio	Better than 50dB(at AGC off)
Power Input Input Voltage DC 12V Vibration 7G Shock 100G	Horizontal Resolution	· · ·
Vibration 7G Shock 100G	Waterproof	ІР69К
Shock 100G	Power Input	Input Voltage DC 12V
	Vibration	7G
Operating Temperature $-40^{\circ}\text{C} \sim +80^{\circ}\text{C}$	Shock	100G
	Operating Temperature	$-40^{\circ}C \sim +80^{\circ}C$
Dimension 69[W] x 41[H] x 52[D] mm	Dimension	69[W] x 41[H] x 52[D] mm
Weight Approx. 230g	Weight	Approx. 230g

Copyright $\textcircled{\mbox{\sc op}}$ 2015. SVS Australia All rights reserved. 02/09/2015

*Conditions apply, visit svsaustralia.com for full warranty conditions

svsaustralia.com